

Specification	AR3a	AR303	Units	Conditions
Frequency Response	39 - 4.5K	32 - 20K	Hz	±3dB @1m
Response Deviation	6.7	2	±dB	40 to 20K Hz, 1/3 oct. in-room @ 1m, typical
Response Deviation	6.7	2.2	±dB	200 to 20K Hz, 1/3 oct. in-room @ 2m, typical
-3 dB Bass Limit	39.0	32.0	Hz	anechoic
-6 dB Bass Limit	33.0	24.5	Hz	anechoic
Midband Sensitivity	89	85	dB	@1m, 2.83 volts
Average Impedance	4.9	6.5	Ω	-
Minimum Impedance	2.7	3.6	Ω	-
Recommended Power	30/150	60/250	W/ch	min/max
THD @ 30 Hz	2.0	1.2	%	85 dB @1m
THD @ 100 Hz	0.35	0.26	%	85 dB @1m
THD @ 1 KHz	0.37	0.31	%	85 dB @1m
Woofers Fs	14	15.2	Hz	-
Woofers Fc	44	41	Hz	-
Woofers Qtc	0.71	0.83	-	-
Internal Volume	38	44	liters	-
Crossover Frequencies	550/6500	650/5500	Hz	electro-acoustic
Size	25x14x11.5	25x15x11	inches	-
Weight	53	54	lbs	-
Price/pr	\$600	\$1,200	US\$	1965 vs. 1994 (CPI= 1:4.2)