



NOTES:

ALL TOLERANCES 10% UNLESS OTHERWISE NOTED
 ALL CAPACITORS 100V 6%DF 10% TOLERANCE NON POLAR ELECTROLYTIC UNLESS NOTED
 BINDING POSTS AND JUMPERS TO BE GOLD PLATED
 WOOFER LEADS 14AWG TWIN LEAD 24" WITH + RED (.205), - BLACK (.110)
 MIDRANGE LEADS 14AWG TWIN LEAD 26" WITH .205 CONNECTORS (+ YELLOW, - BLACK)
 TWEETER LEADS 14AWG TWIN LEAD 28" WITH .205 CONNECTORS (+ BLUE, - BLACK)
 LEADS FROM CUP TO BOARD 14AWG WELL SOLDERED TO BINDING POST OR APPROPRIATE RING TERMINAL
 CROSSOVER MOUNTED ON STANDARD 3" X 5" CUP WITH A PAIR OF 5 WAY BINDING POSTS
 HIGH & LOW + INPUTS AND - INPUTS CONNECTED WITH REMOVABLE JUMPER BARS
 BINDING POSTS TO HAVE METAL NUTS WITH HEX ENDS (1/2" PREFERABLY)
 CROSSOVER CUP TO BE SILK SCREENED WITH SUPPLIED ARTWORK INDICATING HI & LOW INPUTS
 CROSSOVER CUP TO HAVE 6 COUNTERSUNK SCREW MOUNTING HOLES.

AR	Acoustic Research	
	TITLE AR 303a Crossover	
PART NO.	2-12-001-2	FILE NAME 303atmp3.vsc
DATE 07 20 95	DRAWN BY WHR	REVISION 6